

# Coil Rod

Quickly adapt to changing concrete forming conditions by keeping a supply of coil rod on hand



Coil Rod can be used for a variety of concrete forming applications, including form ties, inserts and coil tie combinations.

Coil Rod			
Part No.	Description	Load Rating* (lbs)	Weight/ea (lbs)
SBCR12	Coil Rod 1/2" x 12'	9,000	6.4
SBCR58	Coil Rod 5/8" x 12'	12,000	10.2
SBCR34	Coil Rod 3/4" x 12'	18,000	14.4
SBCR78	Coil Rod 7/8" x 12'	24,000	20.2
SBCR1	Coil Rod 1" x 12'	38,000	25.1
SBCR114	Coil Rod 1-1/4" x 12'	56,000	42.0
SBCR112	Coil Rod 1-1/2" x 12'	68,000	61.8

\* Load Rating based on 2:1 safety factor.

Coil Rods are also available cut-to-size, with left-hand threading and/or electro-galvanized. Contact a SureBuilt representative for pricing and availability.



Coil Nut			
Part No.	Description	Load Rating* Standard (lbs)	Load Rating* Heavy Hex (lbs)
SB361200	Coil Nut 1/2"	6,000	9,000
SBCN58	Coil Nut 5/8"	8,000	12,000
SB361210	Coil Nut 3/4"	9,000	18,000
SBCN78	Coil Nut 7/8"	15,000	24,000
SB361215	Coil Nut 1"	24,000	38,000
SBCN114	Coil Nut 1-1/4"	36,000	56,000
SBCN112	Coil Nut 1-1/2"	47,500	68,000

\* Load Rating based on 2:1 safety factor.

### Coil Rod Coupler

Part No.	Description	Diameter	Length	SWL (lbs) *
SBCRC12	Coil Rod Coupler 1/2"	3/4"	2-3/4"	9,000
SBCRC58	Coil Rod Coupler 5/8"	1"	3-1/4"	12,000
SBCRC34	Coil Rod Coupler 3/4"	1-1/8"	3-1/4"	18,000
SBCRC78	Coil Rod Coupler 7/8"	1-3/8"	4-1/4"	24,000
SBCRC1	Coil Rod Coupler 1"	1-1/2"	4-1/2"	38,000
SBCRC114	Coil Rod Coupler 1-1/4"	1-7/8"	5-3/4"	56,000
SBCRC112	Coil Rod Coupler 1-1/2"	2-1/8"	7"	68,000

\* Safe Working Load (SWL) based on 2:1 safety factor.



*The coil thread has been tapped from each side, providing a positive stop at the center of the coupler.*